

ZKR Versatile Plus

Room Control Unit

Versatile Plus Room Control Unit

This unit ensures communication between Nurse Console and Call buttons in the patient rooms. Room control unit is appropriate for both flush and shallow montage. They have 5" touchscreen, and standard feature allows it to assist total 8 call unit. Due to appropriate hardware, unit can define up to 8 call unit. Modern and durable structure and software ensures the best operating time. When a bed button is touched on the screen, patient information with in the HBYS software can be seen on the unit screen.



Ergonomic Design

5 " Touch Screen

Card Reader

Simple, Easy to Use Interface

High quality flame retardant raw material

Technical specification

ZKRUNCIPRMCN100

Screen size (inches)	120 mm 73 mm 5 inc Touch Screen
Operating system	Linux 4
Weight (g)	500 gr.
Width (mm)	212mm.
Depth (mm)	39 mm.
Height (mm)	165 mm.
Display features	Color Touch Screen, TFT
Screen resolution (px)	800x480
Processor speed	16-24 Bit Flash Microcontrollers 100-Pin
Memory	64MB Ram 128MB Rom
Language	English, Spanish, Russian, Turkish Custom
Power supply	110-220 AC - POE
Operating temperature / Humidity	-10°C +60°C / % 30 %80 RH
Material	PC-ABS-FR (Flame Retardant)
Card reader	MIFARE Classic
Buzzer speaker	2400Hz 65 dB
Input connection	1-Ethernet,1-RS 485, 2.Light Control
Color	White
Communication	TCP / IP - UDP - HTTP - RS485
Current W	18W

Routine control is a standard feature and allows the staff to report what time they have made a room check without a call.

Room control unit's hardware has a card reader. All cards that is read by the unit are asked for authorization check.

